

Gewebe-Warnband

Cloth-Warning-Tape

Beschreibung

Die Sorte 650 ist ein hochqualitatives PE-beschichtetes Gewebeklebeband mit einer sehr hohen Anfangshaftung. Das Klebeband ist reißfest, wasserdicht und sehr strapazierfähig. Es wird hauptsächlich langfristig eingesetzt, kann aber auch kurzfristig eingesetzt werden, da es nach bis zu 7 Tagen von den meisten Untergründen rückstandsfrei entfernbar ist.

Anwendung


Die Sorte 650 wird als Warnband zur Kennzeichnung von gefährlichen Teilen, Maschinen, Geräten, Gebäuden und Flächen eingesetzt.

Product Description

Type 650 is a high-quality PE-coated cloth tape with very high tack. Type 650 is tear- and waterproof and hardwearing. It is mainly used for longterm applications, but can be used also for shorttime, because you can remove it without any residue at many surfaces up to 7 days.

Application

Type 650 is used as warning tape to mark dangerous parts, machines, tools, buildings and places.



Technische Daten

Träger	PE-beschichtetes Gewebe
Gesamtdicke	300 µ
Dehnung bis Bruch	11,5 %
Klebkraft auf Stahl	3,92 N/cm
Zugfestigkeit	64,7 N/cm
Klebstoff	Naturkautschuk
Temperaturbeständigkeit	bis 40° C
Kerndurchmesser	76 mm
Farbe	schwarz/gelb, weiß/rot
Länge	25 m

Technical Data

Backing	PE-coated cloth
Total thickness	300 µ
Elongation at break	11,5 %
Adhesion on steel	3,92 N/cm
Tensile strength	64,7 N/cm
Adhesive	natural rubber
Temperature resistance	up to 40° C
Core diameter	76 mm
Colour	black/yellow, white/red
Length	25 m

Verpackungseinheiten

Bandbreite in mm	Rollen pro Karton
50	24

Packaging

Roll width mm	Rolls per carton
50	24

The information is based on our current knowledge and experience. No guarantee of specific properties or the suitability of the product for a particular purpose can be inferred from our information. All descriptions, drawings, photographs, data, ratios, weights, etc. contained herein are subject to change without notice and do not constitute the contractually agreed quality of the product. Technical changes, dimensional changes, printing errors, and mistakes are reserved.